

DATA SHEET

POLYESTER STRAPPING 15/07

PRODUCT TYPE:		15 X 0,70 GT
<small>Tipo - Typ - Designation - Tipo</small>		GreenTech
CORE (mm) :		405x160
<small>Mandrino - Kern - Mandrin - Mandril</small>		
COLOUR:		GREEN
<small>Colore - Farbe - Couleur - Color</small>		<small>Verde - Gruen - Vert - Verde -</small>
Surface		embossed
<small>Superficie - Oberflaeche - Surface - Superficie</small>		<small>Goffrata - Gerpraegt - Gaufrée - Graffiado</small>
meters/coil (m)		1750
<small>Metraggio/Bobina - Meter/Spule - Metraggi/Borline - Metros/Rollo</small>		<small>± 2,5%</small>
		<small>Maximum, mm</small> 15,50
WIDTH,	Nominal, mm	15,00
	<small>Larghezza - Breite - Largeur - Anchura</small>	<small>Minimum, mm</small> 14,50
		<small>Maximum, mm</small> ,74
THICKNESS,	Nominal, mm	,70
	<small>Spessore - Dicke - Epaisseur - Griueso</small>	<small>Minimum, mm</small> ,66
		<small>Maximum, gr.</small> 10,40
GRAMM METER		Nominal, gr. 10,00
<small>Grammo metro - Gramm meter - Gramme metre - Metro del gramo</small>		<small>Minimum, gr.</small> 9,60
AVERAGE BREAKING STRENGTH,	Kg	320
	<small>Resistenza media - Durchschnittsreifestigkeit - Résistance moyenne -</small>	[N] 3139
		<small>Maximum, %</small> 20
ELONGATION AT BREAK,	Nominal, %	15
	<small>Allungamento - Durchschnittsdehnung - Allongement - Alargamiento</small>	<small>Minimum, %</small> 10
QUALITY STANDARD		UNI EN ISO 9001
<small>Qualità standard - Qualitätsstandard - Standard de qualité -</small>		